# **Document Shredders Model overview**





# With IDEAL shredders you are always on the safe side. Signs you can rely on:



Exceptional quality, reliability and innovative design are what our global customers expect of our products. Benefit from our branded quality Made in Germany supported by a certified Quality Management System according to DIN EN ISO 9001:2015.



Sustainability has always played a major role in IDEAL's corporate philosophy. Only first-class, sustainably produced materials are built into IDEAL products. We have implemented a certified Environmental Management System according to DIN EN ISO 14001:2015 and a certified Energy Management System which proof that we care about the environment.



We offer professional assistance to handle any questions or technical problems. Moreover, we guarantee that even after a device "Made in Germany" has been discontinued, spare parts will remain available for at least 15 years (from model year 2012).



IDEAL shredders are particularly safe and easy to operate. In this connection, the SPS (Safety Protection System) can certainly be seen as an important milestone. SPS features include, for example, a patented, electronically controlled safety flap in the feed opening; automatic reverse and power cut-off (avoids paper jams); automatic stop if the shred bin is full; electronic door protection; double motor protection against overheating.



Robust and durable: the cutting heads of IDEAL shredders are equipped with special hardened, solid steel cutting shafts. We grant a lifetime guarantee of these high-quality cutting shafts under conditions of fair wear & tear (except fine cut and three phase models).



The environmentally-friendly energy saving function of our shredders, the ZERO ENERGY standby mode, ensures automatic and complete power cut-off after 15 minutes.



We set new standards in terms of quality and efficiency through innovative technologies such as the patented ECC – Electronic Capacity Control: this electronic feature indicates the used sheet capacity during shredding process to avoid paper jams.



SSC - Smart Shred Control: That's fun - shredding without paper jams! A smiley on the EASY-SWITCH element has a capacity control function: If it shines green, everything is ok.



Ease of operation: EASY-SWITCH and EASY-TOUCH are intelligent control elements indicating the operational status of the shredder with varying colour codes and back-lit symbols.

# **Automatic oil injection**

### for maximum performance.


The automatic oil injection system lubricates the cutting shafts when shredding and guarantees a constantly high shred performance. Ideal for continuous operation. At the same time, there is the added benefit that the special very environmentally-friendly shredder oil, absorbs shredded-paper dust, thus helping to clean and maintain the cutting shafts.

#### Automatic oiler as an option:

2445, 2604, 3104, 4002 (all cross cut and fine cut models)

#### Automatic oiler as standard:

3105, 4005, 4600, 4606 und 4108 (all strip cut, cross cut and fine cut models)



A Lubricating oil for cutting shafts
Our environmentally-friendly, biodegradable special oil provides for optimum lubrication of the cutting unit.

**B** Solid steel cutting shafts

Regular oiling of the cutting units maintains constant power of the document shredders.

## XXL shredding

# JUMBO models with huge shred bin volume.

Think big: Where other shredders have long since given up, the new JUMBO document shredders from IDEAL are not even close to reaching their limits. These data protectors achieve absolute peak values in terms of both volume and performance. Indeed, the JUMBO units are more than capable of handling the GDPR-compliant destruction of large paper quantities. Above all, they impress with their simply enormous shred bin volume – which guarantees extremely long emptying intervals.





#### 75-litre shred bin volume

Boasting a 75-litre shred bin, the JUMBO IDEAL 2465 model offers double the bin volume of the standard versions.



#### 240-litre shred bin volume

The movable "blue bin" is used as a collection bin. This allows models 2604, 3105 and 4005 to achieve an exceptionally high volume of 240 litres.




#### Height-adjustable feet

Also allow these devices to be positioned in problematic areas, as uneven floor surfaces then present no problems.







# **Deskside shredders**







2220	2245		2265

Model	2220	2245	2245 CC	2245 CC	2265	2265 CC	2265 CC		
Feed opening, mm	220	220	220	220	220	220	220		
Shredder type	strip cut	strip cut	cross cut	cross cut	strip cut	cross cut	cross cut		
Shred width, mm	4	4	3 x 25	2 x 15	4	3 x 25	2 x 15		
Performance in sheets, A4 paper 70 g/m²	11-13	11-13	6-7	4-5	11-13	6-7	4-5		
Performance in sheets, A4 paper 80 g/m²	9-11	9-11	5-6	3-4	9-11	5-6	3-4		
Security level ISO / IEC 21964 (DIN 66399)	P-2	P-2	P-4	P-5	P-2	P-4	P-5		
Shreds also			-	-		-	-		
Paper clip proof solid steel cutting shafts	•	•	•	•	•	•	•		
Lifetime guarantee on the solid steel cutting shafts	•	•	•	•	•	•	•		
Automatic oiler	-		-			-			
Shred speed, m/sec.	0.05	0.05	0.06	0.06	0.05	0.06	0.06		
Volume of cabinet in litres	-	-			20				
Shred bin volume in litres	20		20		20				
Available as JUMBO version	-	-			-				
Power connection, volts / Hz (single phase) <sup>1</sup>	230 / 50 / 1~	230 / 50 / 1~			230 / 50 / 1~				
Motor capacity, W	150	150			150				
Automatic start/stop via photo cell	-		•		•				
Control element	multifunction		EASY-TOUCH		EASY-TOUCH				
SSC – Smart Shred Control	-		-		-				
SPS Safety Protection System:	-		-		-				
- Patented safety flap in the feed opening	mechanical		mechanical		mechanical				
- Automatic reverse / automatic power cut-off	-		•		•				
– Automatic cut-off if shred bin is full	-		-			-			
- Electronic door protection	-		-			-			
- Double motor protection	•		•			•			
– ZERO ENERGY standby mode	-		•			•			
Awarded the "Blue Angel" for high energy efficiency	-		•			•			
Mobile on castors	-		-		-				
Dimensions, mm (H x W x D)	452 x 345 x 215	428 x 345 x 213			516 x 345 x 213				
Weight, kg	6	6.5	7.5	7.5	10.5	11.5	11.5		

<sup>&</sup>lt;sup>1</sup> other voltages available

credit cards
CDs/DVDs











2270 2445 2465 IDEAL 1

2270	2270 CC	2270 CC	2445	2445 CC	2445 CC	2445 MC	2445 SMC	2465	2465 CC	2465 CC	IDEAL 1	
220	220	220	240	240	240	240	240	240	240	240	240	
strip cut	cross cut	cross cut	strip cut	cross cut	cross cut	fine cut	fine cut	strip cut	cross cut	cross cut	cross cut	
4	3 x 25	2 x 15	4	4 x 40	2 x 15	0.8 x 12	0.8 x 5	4	4 x 40	2 x 15	2 x 15	
11-13	6-7	4-5	19-21	13-15	10-12	4-6	4-5	22-24	16-18	11-13	10-12	
9-11	5-6	3-4	16-18	11-13	8-10	3-5	3-4	19-21	13-15	9-11	8-10	
P-2	P-4	P-5	P-2	P-4	P-5	P-6	P-7	P-2	P-4	P-5	P-5	
	□ ⊚	□ ⊚				-	-	<b>□</b> ⊚				
•	•	•	•	•	•	-	-	•	•	•	•	
•	•	•	•	•	•	-	-	•	•	•	•	
	-		-	optional	optional	optional	optional		-		-	
0.05	0.06	0.06	0.07	0.06	0.06	0.07	0.07	0.09	0.10	0.10	0.06	
	20				50			50			25	
20 (p	aper) / 3 (CDs/	CDs/DVDs) 35						35			25	
	-		-				-	•	•	-		
	230 / 50 / 1~		230 / 50 / 1~						230 / 50 / 1~		230 / 50 / 1~	
	150		390					580			390	
	•								•		•	
	multifunction				EASY-SWITCH			EASY-SWITCH			EASY-SWITCH	
	-				•			•			-	
	-				•			•			•	
	mechanical				electronic			electronic			electronic	
	-				•			•			•	
	-				•			•			•	
	-				•				•		•	
							•			•		
	-							•	·	-		
										-		
	-		•				•			-		
	537 x 345 x 22	0		6	35 x 395 x 29	1		635 x 395 x 291			600 x 410 x 240	
12.5	13.0	13.0			21			22 23.5			23.5	

## **Office shredders**







2503

2604

3104

							•				
Model	2503	2503 CC	2503 CC	2604	2604 CC	2604 CC	2604 MC	2604 SMC	3104	3104 CC	3104 CC
Feed opening, mm	260	260	260	260	260	260	260	260	310	310	310
Shredder type	strip cut	cross cut	cross cut	strip cut	cross cut	cross cut	fine cut	fine cut	strip cut	cross cut	cross cut
Shred width, mm	4	4 x 40	2 x 15	4	4 x 40	2 x 15	0.8 x 12	0.8 x 5	4	4 x 40	2 x 15
Performance in sheets, A4 paper 70 g/m²	21-23	16-18	10-12	30-32	25-27	15-17	8-10	5-7	30-32	25-27	15-17
Performance in sheets, A4 paper 80 g/m²	18-20	13-15	8-10	26-28	21-23	13-15	6-8	4-6	26-28	21-23	13-15
Security level ISO / IEC 21964 (DIN 66399)	P-2	P-4	P-5	P-2	P-4	P-5	P-6	P-7	P-2	P-4	P-5
Shreds also	□ ⊚			□ ⊚	□ ⊚		-	-	□ ⊚	□ ⊚	
Paper clip proof solid steel cutting shafts	•	•	•		•	•	-	-	•		
Lifetime guarantee on the solid steel cutting shafts	•	•	•		•	•	-	-	•		
Automatic oiler		-		-	optional	optional	optional	optional	-	optional	optional
Shred speed, m/sec.	0.09	0.10	0.10	0.08	0.10	0.10	0.09	0.09	0.08	0.10	0.10
Volume of cabinet in litres		100	'	125					140		
Shred bin volume in litres	75			100				120			
Available as JUMBO version	-			-				-	-		
Power connection, volts / Hz (single phase) 1		230 / 50 / 1-	~	230 / 50 / 1~					230 / 50 / 1~		
Motor capacity, W		580		640					640		
Automatic start/stop via photo cell		•		•					•		
ECC – Electronic Capacity Control		-		•					•		
Control element		EASY-SWITCI	Н	EASY-SWITCH					EASY-SWITCH		
SPS Safety Protection System:		•		•					•		
- Patented safety flap in the feed opening		electronic		electronic					electronic		
- Automatic reverse / automatic power cut-off		•		•					•		
– Automatic cut-off if shred bin is full		•		•					•		
- Electronic door protection		•								•	
- Double motor protection		•								•	
– Zero energy standby mode		•							•		
Awarded the "Blue Angel" for high energy efficiency		•				•				•	
High quality wooden cabinet, mobile on swivel castors		•		•							
Dimensions, mm (H x W x D)	8	70 x 500 x 3	77		9	26 x 495 x 4	70		9	30 x 538 x 4	70
Weight, kg	30	30.5	30.5			48				52	
1 other veltages available											

<sup>&</sup>lt;sup>1</sup> other voltages available













3105 3804 4002	4005
----------------	------

3105 CC	3105 CC	3105 SMC	3804	3804 CC	3804 CC	4002	4002 CC	4002 CC	4005	4005 CC	4005 CC	4005 MC	4005 SMC
310	310	310	400	400	400	400	400	400	405	405	405	405	405
cross cut	cross cut	fine cut	strip cut	cross cut	cross cut	strip cut	cross cut	cross cut	strip cut	cross cut	cross cut	fine cut	fine cut
4 x 40	2 x 15	0.8 x 5	6	4 x 40	2 x 15	6	4 x 40	2 x 15	6	4 x 40	2 x 15	0.8 x 12	0.8 x 5
40-45	25-30	11-12	25-28	19-22	10-13	39-41	28-30	16-18	50-55	40-45	25-30	15-17	10-11
34-39	21-26	9-10	21-24	16-19	8-11	33-35	23-25	13-15	42-47	34-39	21-26	13-15	8-9
P-4	P-5	P-7	P-2	P-4	P-5	P-2	P-4	P-5	P-2	P-4	P-5	P-6	P-7
<b>□ ◎ □</b>	■ ⊚	-	■ ⊚	■ ⊚			■ ⊚				■ ⊚	-	-
•	•	-	•	•	•	•	•	•	•	•	•	-	-
•	•	-	•	•	•	•	•	•	•	•	•	-	-
	standard			-		-	optional	optional			standard		
0.15	0.15	0.15	0.10	0.13	0.13	0.10	0.13	0.13	0.19	0.15	0.15	0.15	0.18
	180			210			210		210				
	140			165			165		165				
•	•	-		-			-		- •			-	-
	230 / 50 / 1~			230 / 50 / 1~			230 / 50 / 1~		230 / 50 / 1~				
	1600			640		1300					1600		
	•			•		•			•				
	•			•		•					•		
	EASY-SWITCH	l		EASY-SWITCH		EASY-SWITCH					EASY-SWITCH		
	•			•		•					•		
	electronic			electronic			electronic				electronic		
	•		•				•				•		
	•			•			•				•		
	•			•			•		•				
							•						
	•			•			•				•		
	•			•			•				•		
			•			•		•					
11	020 x 548 x 59	70	9	770 x 640 x 59	0	9	70 x 640 x 59	0	1010 x 640 x 590				
	102		79	84	84	82	87	87			115		

# **High capacity shredders**





4600

4606

Model		4600 CC	4600 CC	4606 CC 4606		
Feed opening, mm		460	460	460	460	
Shredder type		cross cut	cross cut	cross cut	cross cut	
Shred width, mm		6 x 50	2 x 15	6 x 50	2 x 15	
Performance in sheets, A4 paper	r 70 g/m²	85-95	35-45	85-95	35-45	
Performance in sheets, A4 paper	r 80 g/m²	74-83	30-39	74-83	30-39	
Security level ISO / IEC 21964 (D	IN 66399)	P-3	P-5	P-3	P-5	
Shreds also						
Shredding head takes soft metal	objects	•	•	•	•	
Guarantee on the cutting shafts		2 years	2 years	2 years	2 years	
Shred speed, m/sec.		0.	17	0.	17	
Oil injection on the cutting shafts	s (standard equipment)	auto	matic	automatic		
Shred collection in		mobile s	shred bin	mobile shred bin		
Capacity for shreds, litres		2	30	230		
Power connection, volts / Hz (thr	ree phase)1	400 / 50 /	3P+N+PE	400 / 50 / 3P+N+PE		
Motor capacity, kW		2	.2	2.2		
Automatic start/stop via photo c	ell		•			
Control element		EASY-S	SWITCH	EASY-SWITCH		
llumination of the working area			•			
Automatic reverse / automatic p	ower cut-off	•	/ •	•/•		
Automatic cut-off if shred bag is	full		•			
Electronic door protection			•			
Thermal overload switch			•			
Automatic standby after 30 minutes			•			
Movable on castors			•			
Dimensions, mm (H x W x D)		1230 x 7	740 x 765	1700 x 740 x 765		
Weight, kg		24	44	253		
Accessories (optional):	Modular conveyor belt system		- -		-	
	Second shred trolley		-		-	
	I .			1		

<sup>1</sup> other voltages available







#### 4108

#### 5009

410 410 410 410 500 500  strip cut cross cut cross cut cross cut cross cut cross cut cross cut 6 6 6 8 50 2 x 15 8 8 x 40-80 6 8 x 50 100-120 85-100 143-48 400-700 300-400 87-105 74-87 37-42 500-600 250-350 P-2 P-3 P-5 P-2 P-3	4108	4108 CC	4108 CC	5009-2 CC	5009-3 CC		
6 6 6 x 50 2 x 15 8 x 40-80 6 x 50 100 100-120 85-100 43-48 600-700 300-400 87-105 74-87 37-42 500-600 250-350 P-2 P-3 P-5 P-2 P-3 P-3 P-3 P-4	410	410	410	500	500		
100-120 85-100 43-48 600-700 300-400 87-105 74-87 37-42 500-600 250-350  P-2 P-3 P-5 P-2 P-3  □ ○ □ □ ○ □ □ □ □ □ □ □ □ □ □ □ □ □ □	strip cut	cross cut	cross cut	cross cut	cross cut		
87-105	6	6 x 50	2 x 15	8 x 40-80	6 x 50		
P-2 P-3 P-5 P-2 P-3  □ ○ □ □ ○ □ □ ○ □ □ ○ □ □ □ □ □ □ □ □	100-120	85-100	43-48	600-700	300-400		
	87-105	74-87	37-42	500-600	250-350		
2 years 0.26 0.21 / 0.12 (variable shred speed >2-MATIC*)  automatic manual suspension for disposable plastic bags with pult-out mechanism on wheels shred trolley  300 300  400 / 50 / 3P-N+PE 400 / 50 / 3P-N+PE  4.0 3.0 3.0 3.0 9.0 (2 x 4.5)	P-2	P-3	P-5	P-2	P-3		
2 years   2 ye		□ 0 🕞	□ ⊙ 🕞				
0.26	•	•	•	•	•		
automatic manual  suspension for disposable plastic bags with pull-out mechanism on wheels shred trolley  300  400 / 50 / 3P+N+PE  4.0 3.0 3.0 3.0 9.0 (2 x 4.5)  EASY-SWITCH panel with push buttons	2 years	2 years	2 years	2 years	2 years		
Suspension for disposable plastic bags with pull-out mechanism on wheels   300   300   300   300   300   300   400 / 50 / 3P+N+PE   4.0   3.0   3.0   3.0   9.0 (2 x 4.5)     -   -   -   -   -   -   -		0.26		0.21 / 0.12 (variable s	hred speed »2-MATIC«)		
300 300  400 / 50 / 3P+N+PE 400 / 50 / 3P+N+PE  4.0 3.0 3.0 9.0 (2 x 4.5)		automatic		ma	nual		
400 / 50 / 3P+N+PE  4.0 3.0 3.0 3.0 9.0 (2 x 4.5)	suspension for di	sposable plastic bags with pull-out mec	hanism on wheels	shred trolley			
4.0 3.0 3.0 3.0 9.0 (2 x 4.5)		300		300			
EASY-SWITCH panel with push buttons		400 / 50 / 3P+N+PE		400 / 50 / 3P+N+PE			
EASY-SWITCH panel with push buttons	4.0	3.0	3.0	9.0 (2 x 4.5)			
		-		<del>-</del>			
.//		EASY-SWITCH		panel with push buttons			
• • • • • • • • • • • • • • • • • • •		•		-			
• • • • • • • • • • • • • • • • • • •		• / •		•/•			
• • • • • • • • • • • • • • • • • • •		•		•			
• - • • • • • • • • • • • • • • • • • •		•		•			
• • 1440 x 1240/690² x 1700 1714 x 1036 x 2170/3070³ 357 1130 • •		•			•		
1440 x 1240/690² x 1700 1714 x 1036 x 2170/3070³ 357 1130 -		•		-			
357 1130 - • •		•		•			
		1440 x 1240/690 <sup>2</sup> x 1700	1714 x 1036	x 2170/3070 <sup>3</sup>			
		357	1130				
		-					
		-		•			



